

Part Number: CC31200C

Product Description: Concealed Side Entry, Lever

Operated Cistern

Applied Standard(s): BS EN 14055

Material(s): ABS, Chrome Plated, HIPS, Nitrile Rubber, POM, PP, PVC, Rubber, Silicon, Stainless Steel

Approx. Weight (kg) 3.000

Product Dimensions 500x135x325

Packaging: Boxed

Product Type: Cistern with Fittings

Product Details:

- Supplied with Fluidmaster syphon for a leak-free flush.
- Supplied with side entry water saving Airgap fill valve.
- Removable lid for top Access into the cistern.
- Internal Overflow.
- Flush pipe, seals, nuts, washers included.
- Outlet thread size 1.5" BSP.
- Quick and simple installation.
- Long length concealed dual flush chrome lever.
- Dimensions – W500 x D135 x H325 (Incl Lid)
- Made From Recyclable Materials.

(Wall fixings not included)



Installation Notes:

- Fill Valve height must be adjusted to overall height of 292mm.
- Overflow Height must be at Lowest Setting
- Full flush setting must be on #6
- Partial Flush Setting must be on #6
- Inlet water supply to the cistern must be 15mm Copper for at least 1m to the valve connection
- Water Level Must be 170mm

End Of Life Data:

Please recycle all components in accordance with local guidelines/facilities.

Product Warranty 12 Months