MAXIE FAUX MOHAIR



TECHNICAL SPECIFICATION SHEET



TECHNICAL INFORMATION



Fire Resistance

Upholstery: BS 7176 Medium Hazard

BS 5852: Part 2 Ignition Source 5 (Crib 5)

When tested over CMHR foam - density approx. 36 kg/m3

IMO: IMO FTPC Part 8 (upholstery)

USA: NFPA 260 Class 1 (UFAC)

CAL 117/13

Composition: 100% Polyester

Width 137 cm

Weight 540g/m2 (FR Back coated)

Martindale 50,000

Wyzenbeek 50,000 Double Rubs (Cotton Duck)

Usage 🛱 🗜

Cleaning

Severe Contract Upholstery

See Cleaning Instructions

Environmental Oeko-Tex, Reach and Pop Compliant

CARE & CLEANING

Thank you for choosing a Sekers upholstery fabric. With the right care and attention, you can help maintain the quality and appearance of your furniture for years to come. Please follow the care and cleaning recommendations below to preserve the beauty and longevity of your fabric.

CLEANING INSTRUCTIONS

Spills: Absorb spills immediately with a clean dry cloth, do not rub.

Stains: Gently dab stains with distilled water, then work from the outside of the stain towards the centre using light circular motions.

Cleaning Agents: Do not use aggressive or chemical-based cleaners that may damage the fabric.

MORE INFO

For further advice or questions about caring for your upholstery, please contact our customer service team.

Sekers Fabrics Ltd www.sekersfabrics.co.uk info@sekersfabrics.co.uk



WWW.SEKERSFABRICS.CO.UK

Tel: +44 (0)1946 517 501

Sales: sales@sekers.co.uk
Export: export@sekers.co.uk

Head Office 7A Nobel Rd Wester Gourdie Industrial Estate Dundee DD2 4UH